



Enterphone Elektra 4

Economical Electronic Directories with Premium Features.

A standalone dialer or an entrance panel for the Enterphone® 2000 "No Phone Bill" System.

- ✦ The quality you need
- ✦ The flexibility you demand
- ✦ At a price you can afford!

viscount

viscount
We Control Doors.

The Enterphone Elektra 4 is a versatile, cost effective telephone entry system. It has a large built-in four line LCD directory that is easy to read in direct sunlight or at night, without additional options.

The Enterphone Elektra 4 can be used independently as a dialer or as a panel for the Enterphone® 2000 system. Please refer to the separate brochure for the additional benefits of the Enterphone 2000.

The Enterphone Elektra 4 is simple to use and simple to program. The user simply scrolls through the electronic directory list to locate a tenant and calls the suite. No messy directory boards are required. The owner can program the unit off the system keyboard or remotely via computer modem making managing the system efficient and effective.

The Enterphone Elektra 4 has many options. This includes connecting up to 4 card readers directly to the unit, thereby bypassing the need for a separate access control system and keeping all programming in one neat package.

FEATURES

Key Features

- Large built-in 4 name LCD directory. Easy to read in direct sunlight or at night, without additional options
- Voice mail response capability. (Keypad active after unit calls out)
- Memory capacity for up to 2000 telephone numbers
- Dials out either touch-tone or rotary, field programmable
- Unit will not accept touch-tone through microphone
- Unit mutes tones in speaker during dialing
- Fully programmable via its own keypad. (ALPHA and NUMERIC)
- 2 programming levels. 6 digit passcode required to make system changes. 3 digit passcode allows only changes in names, codes, phone numbers, PIN's, and cards
- 2 digit passcode allows control of relays
- Talk time field programmable from 1-99 min.
- Postal lock capability included
- Door auto re-lock (door sense)
- Request to exit input (REX)
- Alarm shunt relay
- PIN numbers for keyless entry
- PIN's may be controlled by time zones which are available with the clock/calendar option
- PIN attempts (strike out) 1-9
- Surge protection
- Remote relay activation
- Latching relays
- Programmable background, audible "beep" to indicate call placed from telephone entry unit
- Resident activated door/gate release via touch-tone number, field programmable

Optional Features

- Modem allows programming remotely from a PC. Remote programming can be accomplished on-line, or by uploading/downloading of data
- Card access module allows up to 4 card readers to be connected
- Module accepts Wiegand output readers, such as Proximity, Barium Ferrite, Infrared and Wiegand output keypads and other devices
- Groundstart
- Printer capability RS232 or current loop to printer
- Clock and calendar, timed unlock and relock
- Second control relay package (2nd door)
- Third door control (for CCTV activation, alarm output, and tamper input)
- M.U.I. (multiple unit interface) allows up to 4 Enterphone Elektra 4's to share a single phone line
- Clock option-8 time zones, 8 access levels, and 8 groups can be programmed to further control access
- Special finishes available upon request
- Standby battery charger
- Flush mount

Part Numbers

- **417-T4HF50** - 50 unit spk/mic
- **417-T4HF100** - 100 unit spk/mic
- **417-T4HF250** - 250 unit spk/mic
- **417-T4HF500** - 500 unit spk/mic
- **417-T4HF1000** - 1000 unit spk/mic

SPECIFICATIONS

Dimensions: Door dimensions: 10"w x 14"h x 3"d overall for semi-flush mount. Housing dimensions are: 9 1/2"w x 13 1/2"h x 2 1/4"d

Construction: Front Panel: 16 gauge stainless steel;
Back Box: painted, chemically treated alloy aluminum painted with weather resistant finish

Power Input: 18VAC 40VA UL listed transformer (provided with unit)

Telephone Line: Voice grade RJ11C jack

Operating Environment: Temperature: -20°- +50° C / -4° to +122° F
Relative Humidity: 5% - 95% non-condensing

Relay Output: Form C dry contact 24V @ 3 AMP
Mounting: Surface, flush or pedestal mount

Memory Type: Non-volatile

Tone Detection: Crystal controlled, detects short burst 50 ms. DTMF

Shipping Weight: Approx. 15 lbs.

FCC Reg. #: CPWVSA-73632-MT-E

DOC Canada: 260 4905A

Represented by:



For more information or specifications on Enterphone Elektra 4, contact:
Viscount Communication and Control Systems Inc.

4585 Tillicum Street
Burnaby, B.C., Canada V5J 3J9
Telephone: (604) 327-9446 Toll Free: 1-800-476-3774
Facsimile: (604) 327-3859

E-mail: sales@viscount.com Website: <http://www.viscount.com>