

Enterphone MESH A JWcsYfj Yf 2 50-24-MS2

The Enterphone MESH MicroServer 2 is a bundled appliance that hosts Web-based access control software for facilities requiring up to 64 card readers, elevator control and telephone entry. Each MS2 can act as a standalone visitor entry and access control system or can be used as a distributed database appliance working with other Enterphone MESH MicroServers or Enterphone iQ telephone entry panels.

The Enterphone MESH MicroServer supports card readers through the addition of IP based devices called Enterphone MESH Bridges.

MicroServer Functional Specifications Include:

- 64 readers per MicroServer appliance
- Appliances are interconnected via WAN/LAN
- Unlimited users and cards
- Unlimited administrative users
- Full Access, View Only, and No Access administrative permissions by parameter
- Unlimited schedules and groups
- User selectable event history with purge and/or export
- Open interface to HR and IT database(s)
- Monitors forced entry, door ajar
- Direct connect keyboard and mouse
- Rack mount or wall mount options



System Specifications:

Motherboard	Includes Intel 945GC Atom Processor or better
Flash Drive	4 Gig Solid State Linux Fanless
Power	12VDC to 110 Adapter
Dimensions	Base: 12¼"; height: 3¾"; width: 8½"
Warranty	1 Year; must be installed in a protected environment

Programming is Web-based interface via Ethernet or direct connection

MicroServers run on Linux with an open architecture SQL database.

Call: 604-327-9446

E-mail us at sales@viscount.com or visit us at www.viscount.com

viscount systems